

INSTRUCTIONS FOR MOUNTING THE DOOR PANEL

The refrigerator is normally delivered without door panel(s). Before starting the mounting work check that the panel dimensions are in compliance with those given in the table and read the instructions through. When mounting the panel, proceed as follows.

- A. Remove the top decoration strip (2) with its two screws (1).
- B. Insert one of the vertical edges of the panel into the groove of the door frame (3).
- C. Bend the panel gently so that the free side of the panel can be slipped into the corresponding groove of the door frame (4).
- D. Push the panel downwards so that the lower horizontal edge of the panel is fitted into the bottom groove (5).
- E. Between the upper edge of the panel and the door frame there is now a gap which should be covered by the decoration strip.
- F. Put the strip across the door so that the gap is covered and push it upwards (6).
The tabs on the inside of the strip should fit in behind the flange of the door frame. Secure the decoration strip by means of the two screws (1).

Panel dimensions Thickness max. 5/32"

TYPE	HEIGHT		WIDTH		
	MAX.	MIN.	MAX.	MIN.	
RM 361	648 25 1/2"	645 25 13/32"	535 21 1/16"	532 20 15/16"	mm inch
RM 461	687 27"	684 26 15/16"	569 22 13/32"	566 22 9/32"	mm inch
RM 661	887 34 15/16"	884 34 13/16"	569 22 13/32"	566 22 9/32"	mm inch
RM 761 upper	296 11 21/32"	293 11 17/32"	569 22 13/32"	566 22 9/32"	mm inch
RM 761 lower	809 31 27/32"	806 31 23/32"	569 22 13/32"	566 22 9/32"	mm inch
RM 1301 upper	360 14 3/16"	357 14 1/16"	598,5 23 9/16"	595,5 23 7/16"	mm inch
RM 1301 lower	879 34 5/8"	876 34 1/2"	598,5 23 9/16"	595,5 23 7/16"	mm inch

TO CHANGE THE DOOR OPENING FROM LEFT TO RIGHT OR VICE VERSA

Open the door and unscrew the two screws holding the top front cover. The screws are accessible from beneath. Remove the top hinge pin and lift out the door.

The lower pin for the refrigerator door should be shifted to the opposite side.

The door can then be remounted. Before the top front cover is refitted check that the door closes easily and that the gasket seals well on all sides.

